


FREEWAY™ 035

DRUG-ELUTING PTA BALLOON TECHNOLOGY

SPECIFICALLY DESIGNED FOR PERIPHERAL INTERVENTIONS



PROVEN SAFETY & EFFICACY ^{1, 2, 3, 4}

FREEWAY™ 035 – DRUG-ELUTING PTA BALLOON TECHNOLOGY

SPECIFICALLY DESIGNED FOR PERIPHERAL INTERVENTIONS

COATING

Paclitaxel



Paclitaxel is an active ingredient that inhibits the cell replication thus blocking the microtubules decomposition during the metaphase and anaphase stages of mitosis.

By selectively inhibiting the proliferation of smooth muscle cells, paclitaxel does not influence non-proliferating cells.

Shellac

Shellac is a natural resin composed of shellolic and alleuritic acid. The excellent film forming properties of shellac are used to coat pharmaceutical products and in the food industry.

Investigation of cytotoxicity



SHELLAC DOES NOT SHOW ANY CYTOTOXICITY – SHELLAC IS SAFE.

¹ Peters K, Prinz C, Salomon A et al. "In Vitro Evaluation of Cytocompatibility of Shellac as Coating for Intravascular Devices." Trends Biomater Artif Organ 2012; 26(2):110-11.

FREEWAY™ 035 – DRUG-ELUTING PTA BALLOON TECHNOLOGY


SPECIFICALLY DESIGNED FOR PERIPHERAL INTERVENTIONS

COATING CHARACTERISTICS


The FREEWAY™ 035 bioshell coating matrix consists of a 1:1 mixture of paclitaxel with shellac applied to the balloon surface by a micro-pipetting procedure in a clean room under sterile conditions. Paclitaxel is applied in a final concentration of 3 µg/mm².

In contact with body liquid the hydrophilic shellac matrix of the composite swells and opens the structure for the pressure-induced fast release of paclitaxel from the inflated balloon.


After balloon dilatation, injuries to the arterial wall stimulate inflammatory reaction, the excretion of growth factors and the onset of vascular smooth muscle cell division and migration to the intima. The FREEWAY™ 035 Paclitaxel-eluting PTA balloon catheter delivers a proper concentration of paclitaxel to the arterial wall, thus prevents restenosis and enhances a smooth re-endothelialization process after balloon dilatation.



coated balloon deflated



in contact with blood



inflated balloon allows freed paclitaxel to enter the vessel wall



EFFECTIVE
BIOSHELL
COATING^{2, 3, 4}

FREEWAY™ 035 – DRUG-ELUTING PTA BALLOON TECHNOLOGY



SPECIFICALLY DESIGNED FOR PERIPHERAL INTERVENTIONS

HOW IT WORKS


FREEWAY™ 035, peripheral PTA balloon 0.035" –

An innovative concept with many benefits:


- **Delivers** drug locally over a short period of time
- **Crosses** lesions smoothly due to the low profile
- **Treats** lesions where stents are not a viable solution
- **Enables** re-intervention



PTA causes vessel wall injury. Hyperplasia of the inner vessel wall resulting in lumen narrowing is the natural reaction to this injury.



After predilatation, the FREEWAY™ 035 Paclitaxel-eluting PTA balloon is advanced to the lesion site.



With the balloon well positioned, inflation for at least 120 seconds releases an optimal amount of the anti-proliferative drug.



The balloon is withdrawn as the drug penetrates into the artery wall. Paclitaxel will act immediately, over a short term, to inhibit cell re-growth. The shellac coating remains on the balloon.

FREEWAY™ 035 – DRUG-ELUTING PTA BALLOON TECHNOLOGY

SPECIFICALLY DESIGNED FOR PERIPHERAL INTERVENTIONS

FREEWAY™ 035 PRECLINICAL PROGRAM


FREEWAY™ 035 DEB

Domestic swine femoral arteries (n = 54) underwent percutaneous overstretch balloon dilation, controlled by optical coherence tomography (OCT). Paclitaxel tissue uptake was measured at 1h, 1 and 3 days.

- No delay in endothelialization, no disadvantages in injury and inflammation score compared to standard balloon dilatation (femoral arteries 32 ± 2 days).
- FREEWAY™ 035 DEB demonstrated safety and efficacy in a preclinical model of overstretch injury in peripheral arteries.
- Reaching the effective concentration of paclitaxel in the arterial wall with FREEWAY™ 035 DEB inflation.


Minimum Lumen Diameter (mm)

Minimum lumen diameter of femoral arteries at baseline and 32 days follow-up. FREEWAY™ 035 DEB inhibited fibrin accumulation in the intima and media, **leading to significantly less constrictive remodeling and reduced neointimal hyperplasia** of the injured vessel compared to uncoated balloons².



Area Stenosis (mm²) at FU


Vessels treated with FREEWAY™ 035 DEB show **significantly lower area of stenosis** in at 32 days follow-up compared to uncoated balloon treatment².



Tissue paclitaxel concentration (ng/mg)

Inflation time 120s

Inflation of **120s** with FREEWAY™ DEB leads to long presence and high concentration of paclitaxel in the arterial wall² – crucial for inhibition of neointimal proliferation and restenosis.



² Pavo N, et al. "Coating of intravascular balloon with paclitaxel prevents constrictive remodeling of the dilated porcine femoral artery due to inhibition of intimal and media fibrosis." J MATER SCI-MATER M 2016 27(8): 131.

FREEWAY™ 035 CLINICAL PROGRAM

Evidence for the safety and efficacy of the FREEWAY™ 035 DEB

FREEWAY™ Δ 16.4%
better Primary Patency
at 12 months compared to post-stent
dilatation with standard balloon

FREEWAY Stent Study³

Study type and focus

- randomized multicenter trial in Austria and Germany
- 204 patients with *de novo* or restenotic lesions that needed stent implantation

Main findings at 12 months follow-up

- ① **significantly higher primary patency**
- ② **clearly lower target lesion revascularization rate**
- ③ **significantly better improvement in Rutherford clinical classifications and**
- ④ **proven safety due to low major adverse events rate**

for patients treated with stent + FREEWAY™ 035 DEB compared to stent + standard balloon PTA.

FREEWAY™ Δ 27.3%
better Primary Patency
at 12 months compared to PTA with
standard balloon

PACUBA Trial⁴

Study type and focus

- randomized study in Austria
- 74 patients with in-stent restenosis

Main findings at 12 months follow-up

- ① **significantly higher primary patency**
- ② **clearly lower target lesion revascularization rate**
- ③ **clearly better improvement in Rutherford clinical classifications and**
- ④ **proven safety due to low major adverse events rate**

for patients treated with FREEWAY™ 035 DEB compared to standard balloon PTA.

³ Tacke J et al. "The Freeway Stent Study: the 12 Months results highly favor the use of DEB in combination with stenting." Presentation at CIRSE 2017 (Copenhagen, Denmark)

⁴ Kinstner CM et al. "Paclitaxel-eluting balloon versus standard balloon angioplasty in in-stent restenosis of the superficial femoral and proximal popliteal artery: 1-year results of the PACUBA trial." JACC 2016 9(13): 1386-1392

FREEWAY™ 035 – DRUG-ELUTING PTA BALLOON TECHNOLOGY

SPECIFICALLY DESIGNED FOR PERIPHERAL INTERVENTIONS

ADVANCED PRODUCT FEATURES

FREEWAY™ 035 DEB – balloons for successful peripheral interventions

- Wide spectrum of balloon catheters for treating long, diffuse lesions
 - Up to 230 mm balloon length
- Elaborated catheter technology with good crossability, trackability and pushability for treatment of diffuse lesions
 - Dual-lumen shaft design with hydrophilic lubricious coating on distal shaft
- Precise, controlled dilatation
 - Controlled compliance for accurate balloon vessel sizing
 - Flat shoulders
- Short deflation time



Dual-lumen catheter shaft

Single inflation lumen for fast inflation and deflation times kinking resistant shaft material for crossover procedures



Four-fold wrap balloon

4-folding for 4.0 and 5.0 mm



Five-fold wrap balloon

5-folding for 6.0mm to 8.0mm

TECHNICAL DATA

FREEWAY™ 035 – DRUG-ELUTING PTA BALLOON TECHNOLOGY	
Design	Bilumen design – catheter
Balloon diameter	4.0 / 5.0 / 6.0 / 7.0 and 8.0 mm
Balloon length	20–230 mm
Usable catheter length (tip to strain relief)	80 cm and 135 cm
Guide wire diameter	0.035" (0.91 mm)
Coating	Hydrophilic coating
Balloon material	PA, Polyamid/Nylon
Balloon folding	4-folding for 4 mm and 5 mm 5-folding for 6 to 8 mm
Balloon characteristic	Semi-compliant
Recommended introducer sheath	5 F for 4.0 to 6.0 mm Diameter
	6 F for 6.0 and length ≥ 100 mm
	6 F for 7.0 and 8.0 mm Diameter
Recommended balloon inflation time	120 sec
Nominal pressure	6 atm
Rated burst pressure	Balloon length 20 / 40 / 60 mm Diameter 4–6 mm: 16 atm
	Balloon length 20 / 40 / 60 mm Diameter 7–8 mm: 14 atm
	Balloon length 80 / 100 / 120 / 150 / 190 / 230 mm Diameter 4 mm: 16 atm
	Balloon length 80 / 100 / 120 / 150 / 190 / 230 mm Diameter 5-6 mm: 14 atm
	Balloon length 80 / 100 / 120 / 150 mm Diameter 7–8 mm: 12 atm
	Balloon length 190 / 230 mm Diameter 7 mm: 10 atm
Packaging unit	1 unit

FREEWAY™ 035 – DRUG-ELUTING PTA BALLOON TECHNOLOGY

SPECIFICALLY DESIGNED FOR PERIPHERAL INTERVENTIONS

PRODUCT ORDER INFORMATION

Balloon size diameter × length (mm)	Rated burst pressure (atm)	Recommended introducer sheath (F)	Order number
Usable catheter length 80cm			
4.0 × 20	16	5	335-4020 S
4.0 × 40	16	5	335-4040 S
4.0 × 60	16	5	335-4060 S
4.0 × 80	16	5	335-4080 S
4.0 × 100	16	5	335-40100 S
4.0 × 120	16	5	335-40120 S
4.0 × 150	16	5	335-40150 S
4.0 × 190	16	5	335-40190 S
4.0 × 230	16	5	335-40230 S
5.0 × 20	16	5	335-5020 S
5.0 × 40	16	5	335-5040 S
5.0 × 60	16	5	335-5060 S
5.0 × 80	14	5	335-5080 S
5.0 × 100	14	5	335-50100 S
5.0 × 120	14	5	335-50120 S
5.0 × 150	14	5	335-50150 S
5.0 × 190	14	5	335-50190 S
5.0 × 230	14	5	335-50230 S
6.0 × 20	16	5	335-6020 S
6.0 × 40	16	5	335-6040 S
6.0 × 60	16	5	335-6060 S
6.0 × 80	14	5	335-6080 S
6.0 × 100	14	6	335-60100 S
6.0 × 120	14	6	335-60120 S
6.0 × 150	14	6	335-60150 S
6.0 × 190	14	6	335-60190 S
6.0 × 230	14	6	335-60230 S
7.0 × 20	14	6	335-7020 S
7.0 × 40	14	6	335-7040 S
7.0 × 60	14	6	335-7060 S
7.0 × 80	12	6	335-7080 S
7.0 × 100	12	6	335-70100 S
7.0 × 120	12	6	335-70120 S
7.0 × 150	12	6	335-70150 S
7.0 × 190	10	6	335-70190 S
7.0 × 230	10	6	335-70230 S
8.0 × 20	14	6	335-8020 S
8.0 × 40	14	6	335-8040 S
8.0 × 60	14	6	335-8060 S
8.0 × 80	12	6	335-8080 S
8.0 × 100	12	6	335-80100 S

Balloon size diameter × length (mm)	Rated burst pressure (atm)	Recommended introducer sheath (F)	Order number
Usable catheter length 135cm			
4.0 × 20	16	5	335-4020 L
4.0 × 40	16	5	335-4040 L
4.0 × 60	16	5	335-4060 L
4.0 × 80	16	5	335-4080 L
4.0 × 100	16	5	335-40100 L
4.0 × 120	16	5	335-40120 L
4.0 × 150	16	5	335-40150 L
4.0 × 190	16	5	335-40190 L
4.0 × 230	16	5	335-40230 L
5.0 × 20	16	5	335-5020 L
5.0 × 40	16	5	335-5040 L
5.0 × 60	16	5	335-5060 L
5.0 × 80	14	5	335-5080 L
5.0 × 100	14	5	335-50100 L
5.0 × 120	14	5	335-50120 L
5.0 × 150	14	5	335-50150 L
5.0 × 190	14	5	335-50190 L
5.0 × 230	14	5	335-50230 L
6.0 × 20	16	5	335-6020 L
6.0 × 40	16	5	335-6040 L
6.0 × 60	16	5	335-6060 L
6.0 × 80	14	5	335-6080 L
6.0 × 100	14	6	335-60100 L
6.0 × 120	14	6	335-60120 L
6.0 × 150	14	6	335-60150 L
6.0 × 190	14	6	335-60190 L
6.0 × 230	14	6	335-60230 L
7.0 × 20	14	6	335-7020 L
7.0 × 40	14	6	335-7040 L
7.0 × 60	14	6	335-7060 L
7.0 × 80	12	6	335-7080 L
7.0 × 100	12	6	335-70100 L
7.0 × 120	12	6	335-70120 L
7.0 × 150	12	6	335-70150 L
7.0 × 190	10	6	335-70190 L
7.0 × 230	10	6	335-70230 L
8.0 × 20	14	6	335-8020 L
8.0 × 40	14	6	335-8040 L
8.0 × 60	14	6	335-8060 L
8.0 × 80	12	6	335-8080 L
8.0 × 100	12	6	335-80100 L

Eurocor Tech GmbH
In den Dauen 6a
53117 Bonn
Germany

Phone: +49 (0)228/20 15 0-0
Fax: +49 (0)228/20 15 0-5
info@eurocor.de
eurocor.de

Eurocor Tech GmbH is a wholly owned subsidiary of Opto Eurocor Healthcare Limited and is part of the Opto Circuits Group.
Rev. Nr. 0219 B6 FW035

